

POWER OVER ETHERNET INJECTOR: 18V




Description: Telenet's Midspan POE is a Power-over-Ethernet (Poe) power supply which provides DC power for one Poe-equipped device by "Injecting" DC power through the Spare Pair of the CAT5 (10/100Mbps) Ethernet cable

Installation and Management:

Plug and Play installation. Our POE device automatically supplies inline power. Local Power LED is present

Application Diagram:



Electrical Specifications

Ethernet Connectors	RJ45 Jacks (2)
Ethernet Data Rate	10/100Mbps Ethernet
No. of Ethernet Devices that can be powered	Single
Data Lines	Pair 1: Pins 1/2
	Pair 2: Pins 3/6
CAT-5 Power (Poe) Pin out (Spare Pair)	+ VDC: Pins 4/5
	- VDC: Pins 7/8
Operating Temperature	0° C to +50° C
Max Output Power	30W
Nominal Output Voltage	18V (Typical)
Input	205-255 VAC 50Hz
IEEE 802.3af Compliant	Not applicable

Telenet Systems Pvt. Ltd.

2, Mani Bhuvan, Cama Road, Ghatkopar, Mumbai 400 086, Maharashtra, INDIA

T: +91.22.25138325 / 25158374 F: +91.22.25104911 E: info@telenetsystems.com W: www.telenetsystems.com

Telenet Systems Pvt. Ltd.

2, Mani Bhuvan, Cama Road, Ghatkopar, Mumbai 400 086, Maharashtra, INDIA

T: +91.22.25138325 / 25158374 **F:** +91.22.25104911 **E:** info@telenetsystems.com **W:** www.telenetsystems.com